

Boomlift / Manlift

Used Boom Lift Anaheim - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Keeping workers safe as they access conditions in a higher altitude is priceless. The material handling industry offers many boom lift models. A single operator can control a variety of boom lift models. This equipment became popular in the orchard industry to harvest fruit without having to climb a ladder and balance heavy baskets or pails. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Boom lifts make it much easier to reach high tree tops for collecting fruit. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible This equipment is used in numerous industries including installing telephone poles and lines, maintaining overhead cables and window cleaning applications due to their ability to reach items when it is not practical to situate the machine directly underneath the issue. The articulated boom lift is an example that has numerous joints enabling it to bend over or under items. To enable operators to access many places, these sections of the boom lift can move independently. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. These machines are often seen servicing overhead wires and power lines. Certain models are outfitted with water cannons to be used in firefighting applications. Telescoping sections are available on certain models to extend reach to the maximum. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Electric boom lifts are common for interior jobs due to their quieter options and lack of unhealthy carbon monoxide exhaust. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These models extend upwards and outwards, relying on hydraulics that extend and retract. No second operator is required as the platform operator can extend the lift with the controls. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. There are models on the market capable of reaching over 180 feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Boom lifts can fit through tiny spaces and there are 4WD options on the market. In terms of combining height and reach, telescopic boom lifts are your best bet. Jib Boom lifts that have an extension between the platform and the end of the primary boom are called the jib. This design facilitates an extra hinge or articulation point to enable the platform to move up and down or horizontally. Articulating boom lifts and telescoping boom lifts may have jibs. Articulating models have a joint situated roughly halfway between the wheels and the platform to enable it to reach over an obstacle and then lower again if required. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This model features excellent mobility and is capable of accessing hard to reach areas. The machine can lift up, over and out with ease, making difficult locations easy to work with. The first Genie Z-30/20 articulating Z-boom model was launched in 1985. Thanks to their "up an over" abilities, they have gained the ultimate popularity that continues today. Proper Safety Measures When operating any type of industrial equipment, safety is first and foremost. All known safety hazards must be

known to anyone working within the vicinity. Safe operation of the machine and personal safety must be paramount. Before operating the machine, effective communication and essential safety gear need to be in place. Be aware of any battery gases, engine fuels, combustible items, lit cigarettes or open flames near the machine and do not operate if any flammable or combustible items are present. Have a properly mounted, accessible and visible fire extinguisher mounted within reach. It is important to maintain a clean work space around charging stations and work surfaces since clutter or tools could puncture tires or damage the machine or its components. Daily Maintenance Daily maintenance includes a visual inspection and consulting the maintenance manual to ensure the machine is up to date and will operate safely. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. It is vital to discard oils and solvents safely and efficiently to prevent contaminating the environment. Safety can be increased with proper lighting and adequate ventilation along workbenches and within workshops and garages. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. A large part of keeping the boom lift secure and operational is the maintenance inspection report that ensures the operator is safe and monitors the machine's performance and service. A list of single maintenance procedures that need to be conducted at 50-hour and 150-hour intervals is known as commissioning. Quarterly and annual maintenance is required to be performed throughout the year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Prior to operating your equipment, check your maintenance manual to make sure all of the fluid levels, oil changes, battery life and maintenance are up to date.